



Connection Methods


Connection to PLC equipment (For both models, MONTH type & INTERVAL type)



Connection to External Power Supply (DC Adapter) (MONTH type only)



Warning




Shelf Life and Product Warranty

The shelf life of the Pulsarlube PLC is 1 year from the date of production. Product warranty is limited to original defects in material and workmanship and will not cover any collateral damage due to mishandling, abuse and/or any other inappropriate use of this product. Warranty period is 1 year from the date of purchase.

How to Order

* Must select between NPN and PNP types



Specifications

Specifications	Description
Grease Pouch	60,120,240,480ml
Operating Pressure	Avg. 30kgf/cm ² (425psi) Max. 60kgf/cm ² (850psi)
Power Supply	Power Supply: DC 9V ~ 36V max
Output Current	Max. 1A(1,000mA)
Operating Temperature	-20°C ~ +60°C* (-4°F ~ +140°F) *No battery needed
Available Dispensing Periods	MONTH TYPE : 1, 2, 3 ...10,11,12 Month INTERVAL TYPE : Mode 1, 2...6
Installation Thread Size	3/8" M PT
Installation Types	Single Point / Multi-Point
LCD	Backlit LCD

NOTE Technical information is subject to change without notice.

PRODUCT / PLC MODEL
PULSARLUBE PLC AUTOMATIC LUBRICATOR

ISO9001/14001


BEFORE USE

Thank you for purchasing the Pulsarlube PLC, the electromechanical automatic grease lubricator from Pulsarlube USA, Inc. To ensure the safe operation and proper installation of the Pulsarlube PLC unit, we strongly recommend that you read the following information carefully before use. If you require further information, please contact your local supplier or manufacturer.

Product Details



LCD Display



	Backlit LCD		Backpressure Indication
	Blinks when selected cycle ends		Purge mode in operation

PLC Connecting Cables (colors)		
	VCC (Power Supply Cable)	Blue
	Signal Out (Alarm Signal Cable)	White
	GND (Power Supply Cable)	Black
	Signal In (Operation Signal Cable)	Brown

